



- NOTES:
1. Frame Material - R/C(QMFZ2) designated Zytel 70G33L, manufactured by E.I. Dupont rated 130°C max.
 2. Sensing Toroid - Magnetic Metals P/N 5029 (80% Nickel Iron Alloy Rings) with 1000 turns of coated magnet wire, 40 AWG, 45 Ω +/- 10%, Wire is R/C (OBMW2) type Polysol 155 from Elektrisola or equivalent.
 3. Grounded Neutral Toroid - Magnetic Metals P/N F3006 (Ferrite Material) with 300 turns of coated magnet wire, 40 AWG, 16 Ω +/- 10%, Wire is R/C (OBMW2) type Polysol 155 from Elektrisola or equivalent.
 4. Shield Washer - Material - M6 silicon steel, circular dimensions - 0.36 mm thick, OD=14.48 mm, ID=6.60 mm
 5. Insulator - Material - nylon, circular dimensions - 0.3 mm thick, OD=14.4 mm, ID=6.15 mm
 6. Maximum operating temperature = 85°C
 7. Reset Wire - Rubadue ETFE TEFZEL Wire , UL Style 1558 ,30 AWG, Solid, Blue

REVISIONS
 REV 2 - 12/6/06 - ADDED ADDITIONAL DIMENSIONS, CHG TO METRIC - D.ROLLINS.
 REV 3 - 3/7/07 - ADDED CORE DETAILS TO NOTE 2 & 3, ADDED NOTE 6 - D.ROLLINS.
 REV 4 - 3/20/07 - CORRECTED PIN 5 LOCATION DIMENSION - D.ROLLINS
 REV 5 - 5/3/07 - Changed Pin Size from 0.91 to 0.635, changed material from Zytel 101L to Zytel 70G33L. - D. Rollins
 REV 6 - 5/30/07 - Changed 11.06 dimension to 9.96 - D.ROLLINS
 Rev 7 - 1/15/09 - Changed 9.96 dimension to 9.60, redrawn in ACAD format, Added shield washer insulator.

MATERIAL	
FINISH	
DRAWN D. Rollins	DATE 12/05/06
APPROVED	DATE



GFCI COIL ASSEMBLY

All Dimensions in Millimeters

THIS DRAWING IS THE PROPERTY OF C.A. SPALDING CO. COPIES ARE ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPRATUS WITHOUT WRITTEN PERMISSION.

TOLERANCES
 ± 0.13 mm
 ANGLES ± .5°
 UNLESS OTHERWISE SPECIFIED

A SIZE	DRAWING NUMBER AS5859-01		REV 7
	SHEET NO 1	OF 1	